Proceedings of the 2004 IEEE
International Conference on Robotics & Automation
New Orleans, LA • April 2004

Optimal Control of Multiple Robot Systems with Friction using MPCC

Jufeng Peng
Mathematical Sciences
Rensselaer Polytechnic Institute
Troy, NY 12180
Email: pengj@rpi.edu

Mihai Anitescu
Mathematics and Computer Science
Argonne National Lab
Argonne, IL 60439
Email: anitescu@mcs.anl.gov

Srinivas Akella
Computer Science
Rensselaer Polytechnic Institute
Troy, NY 12180
Email: sakella@cs.rpi.edu

Abstract— **This paper studies optimal control of multiple robot systems with frictional contact. The task is to move the robots into goal regions with specified velocities using external control forces. The robots have nonlinear dynamics, which may arise from the robot body dynamics, friction between robot and environment, and friction between robot and robot. Nonpenetration constraints between robots are imposed, and the robots are assumed rigid. The problem is modeled as a mathematical program with complementarity constraints (MPCC). The MPCC model is solved by using its elastic mode, which is a well-behaved nonlinear programming problem. Preliminary results with this approach are illustrated on example problems. The main contributions of this paper are a novel optimal control model that can deal with friction in the multiple robot system, and application of a new mathematical programming algorithm to solve the MPCC formulation. This optimal control model has potential applications in robot systems with friction, such as multifinger manipulation, manipulation with ropes, and multirobot pushing coordination.**

I. Introduction

Consider a scenario in which a robot hand with multiple fingers is above a table on which multiple coins are resting. The goal is to control the robot fingers so they can manipulate all the coins to specified target regions. Each finger may contact multiple coins, and the coins may contact each other during manipulation. Our long-term goal is to automatically generate optimal controls for such tasks involving multiple objects, friction, and contact.

Coordinating multiple robots with simultaneous kinematic and dynamics constraints has applications in various tasks. Examples include manipulation of multiple objects by multiple fingers [15], manipulation of objects by multiple disk-shaped robots [27], and the manipulation of multiple objects by robots using ropes [5]; a rope can be modeled as a chain of rigid bodies that contact the objects and robots.

This paper addresses the following coordination problem: Given a system of n robots, $\mathcal{A}_1, \ldots, \mathcal{A}_n$, each robot is required to move into a specified target region with a target velocity from its specified initial position and initial velocity. The optimal control problem is to generate the control inputs (the applied external forces) and robot paths so that a cost function, such as completion time or fuel consumption of the robot system, is minimized. The robot's motions must satisfy dynamics constraints, including friction constraints and control constraints, and kinematics constraints, such as collision avoidance or nonpenetration constraints.

We build the optimal control model using a mathematical program with complementarity constraints (MPCC) formulation. We then apply a newly developed mathematical programming algorithm [1] to solve the MPCC by transforming it to a well-behaved nonlinear programming problem known as its elastic mode.

To illustrate the approach, we consider a simplified model in which the robots are circular disks with uniform density. We also assume that the control, which is an external force, can be applied at the center of mass of each robot. The translational support friction force is opposite to the velocity of the disk robot because of the symmetry of the bottom face of the disk robot. The rotational support friction of each robot can be modeled through a damper friction proportional to the mass of the robot. In our paper, only minimum time control is used to illustrate our coordination strategy; however, other objectives can be optimized by just changing the model objective.

Friction is an especially important factor in multiple robot control and manipulation. Contact friction can be described using complementarity constraints [10], [29], [26], [3]. We say that two vectors a and b are complementary ($a \perp b$) if they satisfy the constraints

$$a \geq 0 \quad b \geq 0 \quad a^T b = 0,$$

or equivalently

$$a \geq 0 \quad b \geq 0 \quad a^T b \leq 0.$$

The modeled contact-friction problems are called (linear or nonlinear) complementarity problems and can be expressed in the form

$$F(u, v, w) = 0; \quad u \geq 0, \quad v \geq 0, \quad u^T v \leq 0,$$

where u, v are vectors.

A mathematical program with complementarity constraints (MPCC) formulation is an optimization problem in u, v, w that

has the following complementarity constraints:

$$\begin{array}{lrcl} \text{minimize} & \phi(u,v,w) & & \\ \text{subject to} & F(u,v,w) & = & 0 \\ & u & \geq & 0, \\ & v & \geq & 0, \\ & u^T v & \leq & 0. \end{array}$$

The MPCC is significantly more difficult than the complementarity problem, and solving MPCCs is an active area of research [18]. Recent algorithms to solve MPCCs potentially provide new techniques to solve optimal control problems for multiple robot systems. As such, MPCCs can extend the class of solvable problems beyond the multibody dynamics simulations currently solved by complementarity formulations, although the MPCC model faces the challenge of being trapped in local minima.

II. Related Work

Related work falls into the categories of dynamics for the manipulation of multiple bodies, and motion planning and coordination of multiple robots. For an overview of recent research in robotic manipulation, including pushing, see [19].

Motion planning for multiple robots is a broad research area (see [16] for an overview). Recent efforts have focused on using probabilistic approaches [28], [23], [14], [17]. However, none of these papers addresses system optimization with friction.

Dynamics problems with frictional contact have been extensively studied in the past couple of decades, and complementarity constraints have been shown to be an effective way to model the contact friction [4], [10], [11], [20], [21], [29], [12], [3], [26], [25].

Dynamics problems with frictional contact have been addressed previously by solving the corresponding complementarity problems successfully [10], [29], [26], [3]. However, because of a dramatic increase in the level of difficulty of solving a mathematical problem with complementarity constraints as opposed to solving a complementarity problem, the optimal control problem of a multiple robot system that involves intermittent contact friction has rarely been addressed.

Mathematical programs with complementarity constraints, also known as mathematical programs with equilibrium constraints, are an important class of constrained optimization problem arising in economics and engineering [18]. In general, MPCCs are difficult to solve because of their nonconvexity and lack of constraint qualification [24]. However, it has been recently shown in [7], [6], and [1] that nonlinear programming solvers can solve a large set of MPCCs successfully using their elastic mode formulations, which lumps all complementarity constraints into one nonlinear constraint.

III. Problem Formulation

To describe our multiple robot system, we introduce the notation in Table I, for the planar disk-robots $\mathcal{A}^i$ and $\mathcal{A}^j$ (Figure 1).



Fig. 1. Two-robot system modes: noncontact and contact.

A. Dynamics between Robot and Environment

In this paper, the friction dynamics between each robot and environment is modeled as friction between the robot and a horizontal floor. We decompose the translational friction and rotational friction and approximate them separately. We can show that the translational friction force is opposite to the velocity of the disk robot because of the symmetry of the bottom face of the disk robot. The rotational friction of each robot can be described through a damper friction proportional to the size of the robot.

1) **Translational Friction**
Denote the weight of the robot i by G^i. We have a tangential friction force acting between the body and the floor.

$$f_T^i = \begin{cases} -\mu^i G^i \frac{(\dot{x}^i, \dot{y}^i)^T}{||(\dot{x}^i, \dot{y}^i)||_2} & \text{if } \left|\left|(\dot{x}^i, \dot{y}^i)\right|\right|_2 \neq 0 \\ (\hat{\beta}_1^i, \hat{\beta}_2^i)^T, & \text{if } \left|\left|(\dot{x}^i, \dot{y}^i)\right|\right|_2 = 0. \\ \quad \text{here } \left|\left|(\hat{\beta}_1^i, \hat{\beta}_2^i)\right|\right|_2 \leq \mu^{(i)} G^{(i)} & \end{cases}$$

Here, f_T^i satisfies, among others, a circular constraint that cannot be expressed by a finite number of linear constraints. We follow the standard approach in the robotics literature [22], where the circle is approximated by a equilateral K-polygon $\mathcal{P}$, where K is the number of vertices, whose half-diagonals are the vectors $\vec{l}_k^{if}$. The friction force between the robot and the floor can be described in the dynamics case by using the maximum

TABLE I
NOTATION

Notation	Description
$(\cdot)^i$	property of robot $\mathcal{A}_i$
R	radius
$q = (x, y, \phi)^T$	configuration of robot
$\vec{v}_t = (\dot{x}, \dot{y})^T = (v_x, v_y)^T$	translational velocity
$v_r = \dot{\phi}$	rotational velocity of robot
$\vec{v} = (\dot{x}, \dot{y}, \dot{\phi})^T = (v_t, v_r)^T$	velocity of robot
$\vec{N}^{ij} = \begin{pmatrix} x^j - x^i \\ y^j - y^i \end{pmatrix}$	vector from center of $\mathcal{A}^i$ to center of $\mathcal{A}^j$
$\vec{T}^{ij} = \begin{pmatrix} -(y^j - y^i) \\ x^j - x^i \end{pmatrix}$	tangential vector which is perpendicular to $\vec{N}^{ij}$
$\vec{R}_i^{ij} = R^i \vec{N}_{unit}^{ij}$	vector of the radius i in the normal direction
$\vec{R}_j^{ij} = -R^j \vec{N}_{unit}^{ij}$	vector of the radius j in the normal direction
$o^{ij} = \|\|\vec{N}^{ij}\|\|$	distance between center of $\mathcal{A}^i$ and center of $\mathcal{A}^j$
$\rho^{ij} = o^{ij} - R^i - R^j$	distance between the two disks
c_n^{ij}	scaled magnitude of the normal contact force
$\vec{f}_n^{ij} = c_n^{ij} \vec{N}^{ij}$	contact force from $\mathcal{A}^i$ to $\mathcal{A}^j$,
$\vec{f}_T = \mu c_n \vec{T}^{ij}$	tangential force

dissipation principle [26], [25]:

$$
\begin{aligned}
& f_T^i = \sum_{k=1}^{K} \beta_k^{if} \vec{l}_k^{if} \\
& \text{where } \left(\beta_k^{if}\right)_{k=1,2,\ldots,K} \text{ solve} \\
& \text{minimize } \quad (\sum_{k=1}^{K} \beta_k^{if} \vec{l}_k^{if})^T \left(\dot{x}^i, \dot{y}^i\right)^T \\
& \text{subject to } \sum \beta_k^{if} \leq \mu^i G^i \\
& \beta_k^{if} \geq 0 \quad \text{for } k = 1, 2, \ldots, K.
\end{aligned}
$$

We use the Karush-Kuhn-Tucker optimality condition to represent the solution of the above minimization problem as a complementarity problem:

$$
\begin{aligned}
& f_T^i = \sum_{k=1}^{K} \beta_k^{if} \vec{l}_k^{if}, \quad \text{where} \\
& 0 \leq \beta_k^{if} \quad \perp \quad \vec{l}_k^{if^T} \left(\dot{x}^i, \dot{y}^i\right)^T + \gamma^{if} \geq 0 \\
& \quad \text{for } k = 1, 2, \ldots, K \\
& 0 \leq \mu^i G^i - \sum_{k=1}^{K} \beta_k^{if} \quad \perp \quad \gamma^{if} \geq 0,
\end{aligned}
$$

where γ^{if} is the Lagrange multiplier of the optimality system.

2) **Rotational Friction**
The distributed friction forces will also generate a frictional torque that is the integral of all torques. Since the the friction force is proportional to Mg, the torque induced by the friction forces is proportional to the weight Mg. We approximately model this friction torque as damping friction,

$$\tau_r = -\sigma_d M g \dot{\phi}.$$

B. Kinematics and Dynamics between Robot and Robot

The constraints require that two bodies do not penetrate each other. For the case of two robots considered here, we have that

$$\rho^{ij} = \sqrt{(x^i - x^j)^2 + (y^i - y^j)^2} - R^i - R^j \geq 0.$$

When contact exists, penetration between bodies is prevented by a normal force $\vec{f}_n^{ij}$ along the vector $\vec{N}^{ij}$, with a multiplier, $c_n^{ij} \geq 0$. In other words, the normal force is $c_n^{ij} \vec{N}^{ij}$, although $\vec{N}^{ij}$ is not a unit vector. To completely quantify the contact configuration, and the fact that $c_n^{ij} = 0$ when there is no contact, we use the complementarity constraint

$$0 \leq \rho^{ij} \quad \perp \quad c_n^{ij} \geq 0.$$

In the local coordinate frame of the robot, the tangential force is $\vec{f}_T^{ij} = \alpha^{ij} \vec{T}^{ij}$, where $\vec{T}$ is the tangential vector and α^{ij} is the scaled magnitude of the friction force. Following the generalized coordinate notation in [13], we calculate the relative tangential velocity between body 1 and body 2 as

$$v_T^{ij} = (\Psi(\vec{T}_1^{ij}))^T \left(\dot{x}^j, \dot{y}^j, \dot{\phi}^j, \dot{x}^i, \dot{y}^i, \dot{\phi}^i\right)^T,$$

where $\Psi(\vec{a}) = \begin{pmatrix} \vec{a} \\ \vec{R}_i^{ij} \times \vec{a} \\ -\vec{a} \\ \vec{R}_j^{ij} \times \vec{a} \end{pmatrix}$. Here the two-dimensional cross product $\times$ is defined as $\vec{r} \times \vec{a} = det([r, a])$.

For the Coulomb friction model, the multiplier α^{ij} must satisfy

$$\alpha^{ij} = \begin{cases} \mu^{ij} c_n^{ij} & v_T^{ij} < 0 \\ t, \quad t \in [-\mu^{ij} c_n^{ij}, \mu^{ij} c_n^{ij}] & v_T^{ij} = 0 \\ -\mu^{ij} c_n^{ij} & v_T^{ij} > 0 \end{cases}.$$

Here μ^{ij} is the friction coefficient between bodies $\mathcal{A}^i$ and $\mathcal{A}^j$.

The Coulomb friction model can be represented by using complementarity constraints using the maximum dissipation principle [10], [29], [26], [3]:

$$
\begin{aligned}
0 \leq c_n^{ij} \quad &\perp \quad \rho^{ij} \geq 0 \\
0 \leq \alpha_1^{ij} \quad &\perp \quad \Psi(\vec{T}_1^{ij})^T v^{ij} + \gamma^{ij} \geq 0 \\
0 \leq \alpha_2^{ij} \quad &\perp \quad \Psi(\vec{T}_2^{ij})^T v^{ij} + \gamma^{ij} \geq 0 \\
0 \leq \mu c_n^{ij} - \alpha_1^{ij} - \alpha_2^{ij} \quad &\perp \quad \gamma^{ij} \geq 0
\end{aligned}
$$

where ρ^{ij} is the distance function between the two bodies and $\left|\Psi(\vec{T}_1^{ij})^T v^{ij}\right|$ is the magnitude of the relative tangential velocity at the contact point, γ^{ij} is the Lagrange multiplier which will be equal to $\left|\Psi(\vec{T}_1^{ij})^T v^{ij}\right|$, except for the degenerate cases.

C. The Dynamics Equations

We now write the dynamics equations for robot $\mathcal{A}_j$.

$$\begin{aligned} m^j \dot{v}_t^j &= \sum_{k=1}^{K} \beta_k^{jf} d_k^{jf} + \quad F^j \\ &\quad + \sum_{i \neq j} (\alpha_1^{ij} - \alpha_2^{ij}) \vec{T}^{ij} + \sum_{i \neq j} c_n^{ij} \vec{N}^{ij} \\ I^j \dot{\phi}^j &= \sum_{i \neq j} \vec{R}_j^{ij} \times (-f_n^{ij} - f_T^{ij}) - \sigma_d M^j g \dot{\phi}^j \\ &= \sum_{i \neq j} -\alpha_1^{ij} R^j o^{ij} + \alpha_2^{ij} R^j o^{ij} - \sigma_d M^j g \dot{\phi}^j \end{aligned}$$

In our approach, the external forces $F^i, i = 1, 2, \ldots, n$, represent the control variables. We assume the force on each robot can be applied individually, although the magnitude of the force cannot exceed a specified value F_{max}. The ∞-norm is used in our implementation, that is, $|F_x^i| \leq F_{max}, \quad |F_y^i| \leq F_{max}$, although other norms are easy to accommodate.

D. Mathematical Programs with Complementarity Constraints (MPCC) Formulation for Multirobot System with Approximated Friction

The full minimal time optimal control model for multiple robot coordination is now obtained by combining the contents in the previous subsections. Let $\tilde{z} = (q, v, \gamma, \alpha, \beta, c_n, T_f)$, that is, $\tilde{z}$ is a vector by stacking all variables and the unknown terminal time T_f. The optimal control model can be abbreviated as follows:

$$\begin{aligned} &\text{minimize} \quad T_f \\ &\text{subject to} \\ &\qquad \tilde{M}\dot{\tilde{z}} = \tilde{H}(\tilde{z}) \\ &\qquad \tilde{\mathcal{F}}_2(\tilde{z}) = 0 \\ &\qquad \tilde{\mathcal{F}}_1(\tilde{z}) \leq 0 \\ &\qquad 0 \leq \tilde{G}_1(\tilde{z}) \quad \perp \quad \tilde{G}_2(\tilde{z}) \geq 0 \end{aligned}$$

The dynamics, inequality, equality, and complementarity constraints are described by using appropriate vector functions.

We now use a semi-implicit finite difference discretization method to solve the dynamics equations numerically [3]. The discretized formulation then can be written as:

$$\begin{aligned} &\text{minimize} \quad T_f \\ &\text{subject to} \\ &\qquad Mz = H(z)z \\ &\qquad \mathcal{F}_2(z) = 0 \\ &\qquad \mathcal{F}_1(z) \leq 0 \\ &\qquad 0 \leq G_1(z) \quad \perp \quad G_2(z) \geq 0, \end{aligned} \tag{1}$$

where z is a vector by stacking together all $\tilde{z}^t$ at each time step $t = 1, \ldots, N_s$. The vector functions representing the dynamics, inequality, equality, and complementarity constraints are updated correspondingly. We append the full discretized model in Appendix **A**.

IV. Algorithms for Solving MPCCs

We now define our algorithmic approaches for MPCC.

A. Elastic Mode for a Nonlinear Programming Problem

Given a nonlinear programming problem,

$$\begin{aligned} &\text{minimize} \quad \phi(z) \\ &\text{subject to} \\ &\qquad \mathcal{W}_1(z) \leq 0 \qquad \mathcal{W}_2(z) = 0 \end{aligned} \tag{2}$$

where z is the vector variable, $\phi(z)$ is the objective functions, and $\mathcal{W}_1, \mathcal{W}_2$ are the constraint functions. The elastic mode for a general nonlinear program via an L_1 penalty function can be presented as follows:

$$\begin{aligned} &\text{minimize} \quad \phi(z) + \zeta e^T \epsilon \\ &\text{subject to} \\ &\qquad \mathcal{W}_1(z) \leq \ \epsilon_1 \quad -\epsilon_2 \leq \mathcal{W}_2(z) \leq \ \epsilon_3 \\ &\qquad \epsilon = (\epsilon_1, \epsilon_2, \epsilon_3)^T, \end{aligned} \tag{3}$$

where $e = (1, 1, \ldots, 1)^T$ with appropriate dimension and ζ is a penalty parameter.

Solving an elastic mode of a nonlinear programming problem (3) instead of solving that nonlinear programming problem itself (2) is a penalty approach; the method has proved successful for various nonlinear programming problems [18] [9], especially if the nonlinear programming problem (2) is not well behaved, that is, does not have constraint qualification, which is a necessary condition for convergence of many nonlinear programming algorithms.

B. Solving MPCC Using The Elastic Mode

The MPCC formulation of the discretized nonsmooth coordination problem (1) can be rewritten as follows:

$$\begin{aligned} &\text{minimize} \quad T_f \\ &\text{subject to} \\ &\qquad Mz = H(z)z \\ &\qquad \mathcal{F}_2(z) = 0 \\ &\qquad \mathcal{F}_1(z) \leq 0 \\ &\qquad G_1(z) \geq 0 \quad G_2(z) \geq 0 \\ &\qquad G_1^T(z) G_2(z) \leq 0 \end{aligned} \tag{4}$$

This problem is considerably more difficult to solve than a typical nonlinear program. The difficulty originates in the complementarity constraints, which implies the feasible set does not have an interior. In other words, every feasible solution of the MPCC is on the boundary of the solution set. This difficulty results in the fact that MPCC does not satisfy a constraint qualification. In practical terms, this implies that the linearization of the feasible set may be infeasible arbitrarily close to the solution, which may result in abnormal termination

of most nonlinear programming algorithms, a fact that has been amply demonstrated in practice for many otherwise robust packages.

Nevertheless, it has been recently shown that certain approaches can handle this degeneracy quite well. Of particular interest here is the elastic mode of the MPCC. Let

$$\mathcal{W}_1(z) = \begin{pmatrix} \mathcal{F}_1(z) \le 0 \\ G_1(z) \ge 0 \\ G_2(z) \ge 0 \\ G_1^T(z) G_2(z) \le 0 \end{pmatrix}$$

$$\mathcal{W}_2(z) = \begin{pmatrix} Mz = H(z)z \\ \mathcal{F}_2(z) = 0 \end{pmatrix}.$$

Then MPCC (1) is transformed into the nonlinear programming form (2). Now we can solve the elastic mode of (2), which is a well-behaved problem (3), using standard nonlinear programming solvers.

It was shown in [1] that, under reasonable assumptions and for a sufficiently large but finite penalty parameter, the MPCC and its elastic mode (3) will have the same solution. The main advantage of the elastic mode, however, is that it has a feasible set with nonempty interior. Thus, the main barrier in the path of most solvers is removed.

We give some practical notes about solving the models. Finding an initial feasible solution is critical to the solver performance. We achieve this for our MPCC model by fixing a terminal time T_f large enough for the solver to easily find a solution by solving a complementarity problem. Almost every nonlinear algorithm can be trapped in a local minimum. We implement an inexact algorithm to search for the global optimal solution by reducing the objective. The word *inexact* refers to the fact that the rate of the objective reduction is inexact and adaptive.

V. Experimental Results

We conducted several experiments on multiple robot coordination problems. The MPCC formulation and the inexact reducing-objective algorithm are implemented in AMPL [8]. The resulting models were solved by using SNOPT 6.1 [9], which is a highly effective nonlinear programming solver that uses a smooth augmented Lagrangian merit function and makes explicit provision for infeasibility in the original problem and the quadratic programming subproblems. All runs were made on a Linux workstation with 2 GB memory and four Intel XEON 2.00 GHz CPUs. Table II defines the notation used in all tables of results in this section.

TABLE II
NOTATIONS USED IN THE TABLES OF RESULTS

Symbol	Description
N_r	Number of robots
D_{ef}	Dimension of the external force(s)
N_t	Number of time steps
K	K-polygon approximation for circle
N_v	Number of variables
N_{tc}	Number of total constraints
G_s	Global search solution
LB	Lower bound of the optimal solution
G_t	Global search time (seconds)

The robots have specified initial positions and velocities, and each robot is required to move into a specified goal region or position. The goal orientations of the robots (and objects) are not specified. In the following data tables, the lower bound solutions are obtained based on the bang-bang optimal solutions for individual robots without considering the collision avoidance or nonpenetration constraints. We report only the global search time in the tables; however, the program may find a good local optimal solution using much less time. For some cases, even the first local solution is very close to the final search solution.

We have two test example sets A and B. For examples in set A, robot-floor friction exists, but the robots are not permitted to contact each other. For examples in set B, both robot-robot contact friction and robot-floor friction exist.

1) Set A: Each pair of robots is required to have a minimum safe distance $d_s > 0$. In our experiments, $d_s = 0.01$. See Table III for the problems in set A and Table IV for computational results for set A. We include two examples, A1 and A2, of a system with only one robot to show that the computational solutions are very close to the theoretical results; indeed the computational results are bang-bang solutions. (A1 and A2 are the only two examples that have theoretical solutions in our test examples.) The snapshots of the coordination of six robots with collision avoidance are shown in Figure 2 (Problem A4).

TABLE III
TEST EXAMPLES IN SET A

Problem	N_r	D_{ef}	N_t	K	N_v	N_{tc}
A1	1	2	100	16	4385	2693
A2	1	1	100	16	4385	2693
A3	4	2	50	8	11248	8877
A4	6	2	50	4	20177	17220

TABLE IV
COMPUTATIONAL RESULTS FOR EXAMPLES IN SET A

Problem	G_s	G_t (secs)	LB
A1	9.03	5.8	8.94
A2	9.85	98.45	9.75
A3	9.60	20749.2	8.944
A4	9.71	12605.14	8.94

2) Set B: Robot-robot contact is allowed in the test examples. See Table V for the problems in set B and Table VI for computational results for set B. The snapshots of three robots coordination with contact friction are shown in Figure 3 (Problem B4).

TABLE V
TEST EXAMPLES IN SET B

Problem	N_r	D_{ef}	N_t	K	N_v	N_{tc}
B1	2	2	100	16	10665	7080
B2	3	2	50	16	9392	6564
B3	3	2	50	16	9392	6564
B4	3	2	100	8	11680	9600



Fig. 2. Six robot coordination with robot-floor friction and a robot-robot minimum safe distance $d_s = 0.01$ (Problem A4). The robots have specified initial positions and velocities, and each robot is required to move into a specified goal region or position. The snapshots should be read from left to left to right, top row first.



Fig. 3. Three robot coordination with both robot-robot friction and robot-floor friction (Problem B4). Note the change in orientation arising from robot-robot contact.



Fig. 4. Two disk robots push a larger disk object into a specified target region. Note the local minimum solution contains unnecessary robot movement and rotation.

For all problems, SNOPT finished with a message: *Optimal solution found*. This shows that a Karush-Kuhn-Tucker stationary feasible point has been found for all cases by using the elastic mode, as predicted in [1]. Of course, we have no way of guaranteeing that this point is also a global minimum of the problem.

From Tables IV and VI we note however that the objective function gap between the point that was found by the solver and the lower bound is always smaller than 1 and is sometimes as small as 0.07. This shows that we have obtained a high-quality solution point. It is true that Tables IV and VI also show that the final point was not cheap to compute. In our

TABLE VI

COMPUTATIONAL RESULTS FOR EXAMPLES IN SET B

Problem	G_s	G_t	LB
B1	9.78	3157.97	8.94
B2	9.48	4116.81	8.94
B3	9.39	4834.96	8.94
B4	15.85	4834.96	N/A

experience, however, the results are obtained much faster than by using disjunctive programming or integer programming to compute a local solution point. Indeed, using disjunctive programming to replace the complementarity constraints will result in having to deal with thousands of binary variables for problem A4, which seems an impossible task for the desktop computer, and quite possibly for any current computing architecture.

In our experiments, there are some situations that are problematic, and it is worthwhile to mention them.

1) The local minimum solution of the MPCC model may create unsatisfactory behavior, such as unnecessary robot movement and rotation. This is illustrated by the example in Figure 4, where two disk robots push a larger object.
2) The discrete time stepping formulation may introduce unrealistic behavior, especially when the time step is relatively large. The time duration of a physical normal contact force for elastic bodies may be much shorter than the time step, therefore the computed impulse may be much larger than the physical impulse. Another unrealistic behavior is the penetration between robot and robot (or between robot and object) during the interval between discrete time steps, even though there is no penetration at the evaluated time instances. Decreasing the time steps may reduce these unrealistic behaviors; however this will increase the problem complexity.

VI. CONCLUSIONS

We built a novel optimal control model for coordinating multiple robots with friction based on mathematical program with complementarity constraints (MPCC). A new mathematical programming algorithm was applied to solve the MPCC problem by solving the elastic mode of this MPCC problem. Numerous dynamics simulations of multibody systems with contact friction have been studied previously in robotics and mechanics. However, we are not aware of any previous work on optimal control of multiple robot systems involving contact friction.

MPCCs are a convenient way to represent the optimal control model for robot systems with friction. Our preliminary results show that solving MPCCs is computationally challenging, though it still compares favorably with most other choices, in particular disjunctive or integer programming approaches. Therefore we believe that an important future direction is improving the efficiency of algorithms to solve MPCCs.

The approach presented here can be immediately extended, in principle, to problems that have robots of other smooth shapes, for example elliptical. For such shapes, the depth of penetration function is smooth [2]. In addition, the depth of penetration can be represented by adding a few other constraints that involve the shape of the bodies. Extending the model to 3D is a natural next step, although we expect more computational challenges. Studying simpler problems, for example, where control can only be applied at the initial state, may give us theoretical guarantees of faster convergence. The MPCC formulation is also potentially applicable to a broader class of problems, for example, motion planning problems with static and moving obstacles. The minimum distance between each obstacle and robot can in general be represented using complementarity constraints. Therefore certain motion planning problems that involve minimum distance constraints can be solved as MPCCs. Additionally, it will be interesting to look at optimal control problems for hybrid systems that can be modeled as complementarity systems.

ACKNOWLEDGMENTS

Jufeng Peng was supported in part by the Givens Associate Fellowship with the MCS Division, Argonne National Laboratory. Mihai Anitescu was supported through Contract No. W-31-109-ENG-38 with the U.S. Department of Energy. Srinivas Akella and Jufeng Peng were supported in part by NSF Award IIS-0093233.

REFERENCES

[1] M. Anitescu. On solving mathematical programs with complementarity constraints as nonlinear programs. Preprint ANL/MCS-P864-1200, Argonne National Laboratory, Argonne, Illinois, 2000.

[2] M. Anitescu, J. F. Cremer, and F. A. Potra. Formulating 3d contact dynamics problems. *Mechanics of Structures and Machines*, 24(4):405–437, 1996.

[3] M. Anitescu and F. A. Potra. Formulating dynamic multi-rigid-body contact problems with friction as solvable linear complementarity problems. *Nonlinear Dynamics*, 14:231–247, 1997.

[4] D. Baraff. Issues in computing contact forces for non-penetrating rigid bodies. *Algorithmica*, 10:292–352, 1993.

[5] B. R. Donald, L. Gariepy, and D. Rus. Distributed manipulation of multiple objects using ropes. In *IEEE International Conference on Robotics and Automation*, pages 450–457, San Francisco, CA, April 2000.

[6] R. Fletcher and S. Leyffer. Numerical experience with solving MPECs as NLPs. Technical Report NA 210, Department of Mathematics and Computer Science, University of Dundee, Dundee DD1 4HN, UK, August 2002.

[7] R. Fletcher, S. Leyffer, D. Ralph, and S. Scholtes. Local convergence of SQP methods for mathematical programs with equilibrium constraints. Technical Report NA 209, Department of Mathematics and Computer Science, University of Dundee, Dundee DD1 4HN, UK, May 2002.

[8] R. Fourer, D. M. Gay, and B. W. Kernighan. *AMPL: A Modeling Language for Mathematical Programming*. Duxbury Press, 1993.

[9] P. E. Gill, W. Murray, and M. A. Saunders. SNOPT: An SQP algorithm for large-scale constrained optimization. *SIAM Journal on Optimization*, 12(4):979–1006, 2002.

[10] C. Glocker and F. Pfeiffer. An LCP-approach for multibody systems with planar friction. In *Proceedings of the CMIS 92 Contact Mechanics Int. Symposium*, pages 13 – 30, Lausanne, Switzerland, 1992.

[11] C. Glocker and F. Pfeiffer. Multiple impacts with friction in rigid multibody systems. *Nonlinear Dynamics*, 7:471–497, 1995.

[12] E. Haug, S. Wu, and S.M.Yang. Dynamic mechanical systems with coulomb friction, stiction, impact and constraint addition-deletion i: Theory. *Mechanisms and Machine Theory*, 21(5):407–416, 1986.

[13] E. J. Haug. *Computer Aided Kinematics and Dynamics of Mechanical Systems*. Allyn and Bacon, Boston, 1989.

[14] D. Hsu, R. Kindel, J. Latombe, and S. Rock. Randomized kinodynamic motion planning with moving obstacles. *International Journal of Robotics Research*, 21(3):233–255, march 2002.
[15] M. Kaneko and K. Harada. Grasp and manipulation of multiple objects. In J. M. Hollerbach and D. E. Koditschek, editors, *Robotics Research: The Ninth International Symposium*, pages 33–39, London, 2000. Springer-Verlag.
[16] J.-C. Latombe. *Robot Motion Planning.* Kluwer Academic Publishers, Norwell, MA, 1991.
[17] S. M. LaValle and J. J. Kuffner. Randomized kinodynamic planning. *International Journal of Robotics Research*, 20(5):378–401, May 2001.
[18] Z.-Q. Luo, J.-S. Pang, and D. Ralph. *Mathematical Programs with Equilibrium Constraints*. Cambridge University Press, Cambridge, 1996.
[19] M. T. Mason. *Mechanics of Robotic Manipulation*. MIT Press, Cambridge, MA, 2001.
[20] J. J. Moreau. Standard inelastic shocks and the dynamics of unilateral constraints. In G. D. Piero and F. Macieri, editors, *Unilateral Problems in Structural Analysis*, pages 173–221, Wien - New York, 1983. CISM Courses and Lectures no. 288.
[21] J. J. Moreau. Unilateral constraints and dry friction in finite freedom dynamics. In J. Moreau and P. Panagiotopoulos, editors, *Nonsmooth Mechanics and Applications*, pages 1–82, Wien - New York, 1988. CISM Courses and Lectures no. 302, Springer - Verlag.
[22] R. M. Murray, Z. Li, and S. S. Sastry. *A Mathematical Introduction to Robotic Manipulation*. CRC Press, Boca Raton, FL, 1994.
[23] G. Sanchez and J.-C. Latombe. Using a PRM planner to compare centralized and decoupled multi-robot systems. In *IEEE International Conference on Robotics and Automation*, Washington, D.C., May 2002.
[24] H. Scheel and S. Scholtes. Mathematical programs with complementarity constraints: stationarity, optimality, and sensitivity. *Mathematics of Operations Research*, 25(1):1–22, 2000.
[25] D. E. Stewart. Rigid-body dynamics with friction and impact. *SIAM Review*, 42(1):3–39, 2000.
[26] D. E. Stewart and J. C. Trinkle. An implicit time-stepping scheme for rigid-body dynamics with inelastic collisions and coulomb friction. *International Journal for Numerical Methods in Engineering*, 39:2673–2691, 1996.
[27] A. Sudsang, F. Rothganger, and J. Ponce. Motion planning for disc-shaped robots pushing a polygonal object in the plane. *IEEE Transactions on Robotics and Automation*, 18(4):550–562, 2002.
[28] P. Švestka and M. H. Overmars. Coordinated motion planning for multiple car-like robots using probabilistic roadmaps. In *IEEE International Conference on Robotics and Automation*, pages 1631–1636, Nagoya, Japan, May 1995.
[29] J. Trinkle, J.-S. Pang, S. Sudarsky, and G. Lo. On dynamic multi-rigid-body contact problems with coulomb friction. *Zeithschrift fur Angewandte Mathematik und Mechanik*, 77:267–279, 1997.

The submitted manuscript has been created by the University of Chicago as Operator of Argonne National Laboratory ("Argonne") under Contract No. W-31-109-ENG-38 with the U.S. Department of Energy. The U.S. Government retains for itself, and others acting on its behalf, a paid-up, nonexclusive, irrevocable worldwide license in said article to reproduce, prepare derivative works, distribute copies to the public, and perform publicly and display publicly, by or on behalf of the Government.

Appendix A: Discretized Optimal Control Model for Multiple Robot Coordination Using MPCC

$$\min \quad T_f$$

subject to *(at each time step t)*

dynamics constraints of disk-robot $\mathcal{A}^i$ and floor

$$0 \le \beta_k^{if,t} \quad \perp \quad (d_k^{if})^T \cdot v^{if,t+1} + \gamma^{if,t} \ge 0 \quad k = 1 \dots K$$

$$0 \le (\mu g M^i - \sum_{k=1}^{K} \beta_k^{if,t}) \quad \perp \quad \gamma^{if,t} \ge 0$$

nonpenetration between $\mathcal{A}^i$ and $\mathcal{A}^j$:

$$\rho^{ij,t} = \sqrt{(x^{j,t} - x^{i,t})^2 + (y^{j,t} - y^{i,t})^2} - R^i - R^j \ge 0$$

dynamics related to $\mathcal{A}^i$ and $\mathcal{A}^j$

$$\vec{N}^{ij,t} = \begin{pmatrix} x^{j,t} - x^{i,t} \\ y^{j,t} - y^{i,t} \end{pmatrix}$$

$$o^{ij,t} = \sqrt{(x^{j,t} - x^{i,t})^2 + (y^{j,t} - y^{i,t})^2}$$

$$\rho^{ij,t} = o^{ij,t} - R^i - R^j$$

$$0 \le c_n^{ij,t} \quad \perp \quad \rho^{ij,t}(q) \ge 0$$

$$\begin{aligned}\Psi(\vec{T}_1^{ij}) v^{ij,t+1} = & -(y^{j,t} - y^{i,t}) v_x^{j,t+1} + (x^{j,t} - x^{i,t}) v_y^{j,t+1} \\ & - R^j o^{ij,t} v_\phi^j + (y^{j,t} - y^{i,t}) v_x^{i,t+1} \\ & - (x^{j,t} - x^{i,t}) v_y^{i,t+1} - R^i o^{ij,t} v_\phi^i\end{aligned}$$

$$\begin{aligned}\Psi(\vec{T}_2^{ij}) v^{ij,t+1} = & (y^{j,t} - y^{i,t}) v_x^{j,t+1} - (x^{j,t} - x^{i,t}) v_y^{j,t+1} \\ & + R^j o^{ij,t} v_\phi^j - (y^{j,t} - y^{i,t}) v_x^{i,t+1} \\ & + (x^{j,t} - x^{i,t}) v_y^{i,t+1} + R^i o^{ij,t} v_\phi^i\end{aligned}$$

$$0 \le \alpha_1^{ij,t} \quad \perp \quad \Psi(\vec{T}_1^{ij})^T \cdot v^{ij} + \gamma^{ij,t} \ge 0$$

$$0 \le \alpha_2^{ij,t} \quad \perp \quad \Psi(\vec{T}_2^{ij})^T \cdot v^{ij} + \gamma^{ij,t} \ge 0$$

$$0 \le \mu c_n^{ij,t} - \alpha_1^{ij} - \alpha_2^{ij,t} \quad \perp \quad \gamma^{ij,t} \ge 0$$

time stepping

$$h = \frac{T_f}{N_s}$$

the kinematics equations

$$\begin{pmatrix} x^{j,t+1} - x^{j,t} \\ y^{j,t+1} - y^{j,t} \end{pmatrix} = v^{j,t+1} h$$

the dynamics equations

$$\begin{aligned}\frac{M^j (v_t^{j,t+1} - v_t^{j,t})}{h} = & \sum_{k=1}^{K} \beta_k^{jf,t} d_k^{jf,t} + \quad F^{j,t} \\ & + \sum_{i \ne j} (\alpha_1^{ij,t} - \alpha_2^{ij,t}) \vec{T}^{ij,t} + \sum_{i \ne j} c_n^{ij,t} \vec{N}^{ij,t}\end{aligned}$$

$$\begin{aligned}I^j \frac{(v_r^{j,t+1} - v_r^{j,t})}{h} &= \sum_{i \ne j} \vec{R}_j^{ij,t} \times (-f_n^{ij,t} - f_T^{ij,t}) - \sigma_d M^j g v_r^{j,t} \\ &= \sum_{i \ne j} -\alpha_1^{ij,t} R^j o^{ij,t} + \alpha_2^{ij,t} R^j o^{ij,t} - \sigma_d M^j g v_r^{j,t}\end{aligned}$$

external force constraints

$$|F_x^{i,t}| \le f_{max} \qquad |F_y^{i,t}| \le F_{max}^i$$

the given initial values

$$q^{i,0} = q_0^i \qquad v^{i,0} = v_0^i$$

the box-constrained final values

$$q_{low,end}^i \le q^i(T_f) \le q_{upp,end}^i$$

$$v_{low,end}^i \le v^i(T_f) \le v_{upp,end}^i$$